

NEW


DC Inverter



COMPACT 4-WAY CASSETTE

COMPACT DESIGN, EASY INSTALLATION

Extremely compact casing suits any room's decor and requires little space for installation on a low ceiling. Due to the compact body and light weight, all models can be installed without a hoist.




360° AIRFLOW

The Compact Four-way Cassette's 360° air outlets provide strong airflow circulation to cool or heat every corner of a room and evenly control temperature.



HIGH-LIFT DRAIN PUMP

A drain pump with a 500mm pump head is fitted as standard.



technical data

Q4AN-2-XMi D22÷D45

4-WAY COMPACT CASSETTE						
Size	Q4AN-2-XMi	D22	D28	D36	D45	
Cooling ⁽¹⁾	Capacity	kW	2,2	2,8	3,6	4,5
	Power input	W	35	35	40	50
Heating ⁽²⁾	Capacity	kW	2,4	3,2	4,0	5,0
	Power input	W	35	35	40	50
Pipe connections	Liquid pipe	mm	Ø 6,35	Ø 6,35	Ø 6,35	Ø 6,35
	Gas pipe	mm	Ø 12,7	Ø 12,7	Ø 12,7	Ø 12,7
	Drain pipe	mm	OD Ø 32	OD Ø 32	OD Ø 32	OD Ø 32
Main body	Dimensions (Width x Height x Depth) ⁽⁵⁾	mm	630x260x570	630x260x570	630x260x570	630x260x570
	Weight	kg	18	18	19,2	19,2
Panel	Dimensions (Width x Height x Depth)	mm	647x50x647	647x50x647	647x50x647	647x50x647
	Weight	kg	2,5	2,5	2,5	2,5
Air flow rate ⁽³⁾		m ³ /h	576/552/524/503 462/441/405	576/552/524/503 462/441/405	604/573/541/516 478/434/400	604/573/541/516 478/434/400
Sound pressure level ⁽³⁾⁽⁴⁾		dB(A)	35/34/33/29 26/23/22	35/34/33/29 26/23/22	41/38/35/32 30/29/28	41/38/35/32 30/29/28
Sound power level ⁽³⁾⁽⁴⁾		dB(A)	51/50/49/45 42/39/38	51/50/49/45 42/39/38	56/53/50/47 45/44/43	56/53/50/47 45/44/43
Power supply		V/Ph/Hz	220-240/1/50			

Notes

- (1) Indoor temperature 27°C DB/19°C WB; Outdoor temperature 35°C DB/24°C WB. Piping length: Interconnecting piping length is 7,5m, level difference is zero.
- (2) Indoor temperature 20°C DB/15°C WB; Outdoor temperature 7°C DB/6°C WB. Piping length: Interconnecting piping length is 7,5m, level difference is zero.
- (3) Data refer to the 7 fan speeds, in descending order.
- (4) Sound values are measured in a semi-anechoic room, at a position 1,4m below the unit.
- (5) Unit body dimensions given are the largest external dimensions of the unit, including hanger attachments

accessories

- ▶ **RM12D** Wireless remote controller
- ▶ **WDC-86E/KD** Compact wired controller
- ▶ **WDC-120G/WK** Wired controller
- ▶ **CE-MBQ4-03B5** Panel 4-way compact

Data contained in this document are not binding and may be changed by the Manufacturer without notice.

www.clivet.com

REF-DG19B015GB-00