

NEW

DC Inverter



CONSOLE

HIGH COMFORT

A wide-angle swing together with auto swing louvers and five fan speed options ensure that airflow reaches every corner of the room. A 2000-stage element mechanical expansion valve ensures precise flow control whilst generating little modulation noise.

FLEXIBILITY

The Console unit can be installed on the floor or lower part of the wall. Full capacity is still achieved even when the underside air inlet is unavailable.

TWO AIR OUTLETS AND FOUR AIR INLETS

The Console unit's combination of four air inlets and two air outlets ensure that cooling and heating is distributed in all directions.



technical data

DNB-2-XMi D22÷D45

Size		DNB-2-XMi	D22	D28	D36	D45
Cooling ⁽¹⁾	Capacity	kW	2,2	2,8	3,6	4,5
	Power input	W	20	25	25	35
Heating ⁽²⁾	Capacity	kW	2,6	3,2	4,0	5,0
	Power input	W	20	25	25	35
Pipe connections	Liquid pipe	mm	Ø 6,35	Ø 6,35	Ø 6,35	Ø 6,35
	Gas pipe	mm	Ø 12,7	Ø 12,7	Ø 12,7	Ø 12,7
	Drain pipe	mm	OD Ø 16	OD Ø 16	OD Ø 16	OD Ø 16
Dimensions (Width x Height x Depth) ⁽⁵⁾		mm	700x600x210	700x600x210	700x600x210	700x600x210
Weight		kg	14	15	15	15
Air flow rate ⁽³⁾		m ³ /h	430/401/374/345 302/268/229	510/482/456/430 355/286/229	510/482/456/430 355/286/229	660/614/561/512 478/436/400
Sound pressure level ⁽³⁾⁽⁴⁾		dB(A)	38/36/34/32 28/27/26	39/37/35/33 31/29/27	39/37/35/33 31/29/27	42/41/40/39 37/36/36
Sound power level ⁽³⁾⁽⁴⁾		dB(A)	54/52/50/48 44/43/42	55/53/51/49 47/45/43	55/53/51/49 47/45/43	58/57/56/55 53/52/52
Power supply		V/Ph/Hz	220-240/1/50			

- Notes**
- (1) Indoor temperature 27°C DB/19°C WB; Outdoor temperature 35°C DB/24°C WB. Piping length: Interconnecting piping length is 7,5m, level difference is zero.
 - (2) Indoor temperature 20°C DB/15°C WB; Outdoor temperature 7°C DB/6°C WB. Piping length: Interconnecting piping length is 7,5m, level difference is zero.
 - (3) Data refer to the 7 fan speeds, in descending order.
 - (4) Sound values are measured in a semi-anechoic room, at a position 1m in front and 1m below the unit.
 - (5) Unit body dimensions given are the largest external dimensions of the unit, including hanger attachments

accessories

- ▶ **RM12D** Wireless remote controller
- ▶ **WDC-86E/KD** Compact wired controller
- ▶ **WDC-120G/WK** Wired controller

Data contained in this document are not binding and may be changed by the Manufacturer without notice.

www.clivet.com

REF-DG198015GB-00